A Major-Project report on

# "High Reactive Power Compensation Accuracy for cascaded H-Bridge Inverter Based Decoupling"

Submitted to

#### Jawaharlal Nehru Technological University, Hyderabad

In partial fullfilment of the academic requirements for the award of Degree of

**BACHELOR OF TECHNOLOGY** 

In

#### **ELECTRICAL &ELECTRONICS ENGINEERING**

Ву

S.HARITHA 206Y5A0224

B.KALA RANI 196Y1A0201

S.ANVITHA 796Y1A0214

G.HARSHINI 206Y5A0207

Under the esteemed guidance of

Mr. R.SHASHI KUMAR REDDY<sub>M.Tech</sub>

**Assistant Professor** 



#### DEPARTMENT OF ELECTRICAL & ELECTRONICS ENGINEERING





2022-23





## DEPARTMENT OF ELECTRICAL & ELECTRONICS ENGINEERING



### **CERTIFICATE**

This is to certify that the major project entitled "High Reactive Power Compensation Accuracy For Cascaded H-Bridge Inverter Based Decoupling" submitted to JNTUH carried out by the following students of IV-B.Tech in the partial fulfillment for the award of the B.Tech Degree in Electrical&Electronics Engineering during the academic year 2022-23.

S.HARITHA

**B.KALA RANI** 

S.ANVITHA

**G.HARSHINI** 

206Y5A0224

196Y1A0201

196Y1A0214

206Y5A0207

R.S. b. Reddy Guide

Mr. R.Shashi kumar Reddy

Head of the Dept

Dr. K. Mahender Sharma



Sumathi Reddy Institute of Tiechnology for Women Ananthasagar (V), Hasanparthy (M) WARANGAL- 506 371 (T.S.)

#### **ABSTRACT**

The Static Synchronous Compensator (STATCOM) has gained popularity among many utilities for solving power quality problems in distribution substations. There are many types of topologies for STATCOM found in the literature, of which the Multilevel Cascaded H-bridge Inverter (MCHI) is the most adaptable and energy efficient power inverter topology. The aim of this paper is to define a control scheme and its transfer function in order to achieve low switching frequency and high-bandwidth power control of MCHI. The controller of the proposed STATCOM system is implemented to provide vector control for reactive power or Voltage-Ampere Reactive (VAR) compensation at the Point of Common Coupling (PCC) under balanced loading conditions. To accomplish this, mathematical equations for a STATCOM system is derived in dq-coordinates based on Park's transformation. Then, the designed equations are used to calculate appropriate values of the controller's gain parameters for realizing the cascade Pulse Width Modulation (PWM) STATCOM with various voltage and current ratings. Lastly, the performance of the proposed control scheme is verified through simulation and numerical analysis using MATLAB-Simulation link.



Principal
Sumathi Reddy Institute of Technology for Women
Ananthasagar (V), Hasanparthy (M)
WARANGAL - 506 371 (TS)