A Major-Project report on

# "Dual-T-Type Five-Level Cascaded Multilevel Inverter with Double Voltage Boosting Gain"

Submitted to

Jawaharlal Nehru Technological University, Hyderabad

In partial fulfilment of the academic requirements for the award of Degree of

#### **BACHELOR OF TECHNOLOGY**

In

**ELECTRICAL & ELECTRONICS ENGINEERING** 

By

G. AKSHITHA BAI N. SHRIYA HASINI E. CHAITANYA S. MANISHA 206Y5A0209 196Y1A0209 206Y5A0206 196Y1A0215

Under the esteemed guidance of

Mrs. P. SUCHARITHA M.Tech

**Assistant Professor** 



## **DEPARTMENT OF ELECTRICAL & ELECTRONICS ENGINEERING**



**SUMATHI REDDY** INSTITUTE OF TECHNOLOGY FOR WOMEN

Affiliated to JNTUH - Approved by AICTE - Accredited by NBA



2022-23

PRINCIPAL Sumathi Reddy Institute of Technology for Woman Ananthasagar (V), Hasanparthy (M) WARANGAL - 506 371 (T.S.)



## DEPARTMENT OF ELECTRICAL & ELECTRONICS ENGINEERING



CERTIFICATE

This is to certify that the major project entitled "Dual-T-Type Five-Level **Cascaded Multilevel Inverter With Double Voltage Boosting Gain**" submitted to JNTUH carried out by the following students of IV-B.Tech in the partial fulfillment for the award of the B.Tech Degree in Electrical & Electronics Engineering during the academic year 2022-23.

G. AKSHITHA BAI N. SHRIYA HASINI E. CHAITANYA S. MANISHA 206Y5A0209 196Y1A0209 206Y5A0206 196Y1A0215

Mrs. P. Sucharitha



Head the Dept Dr. K. Mahender Sharma

PRINCIPAL Sumathi Reddy Institute of Technology for Women Ananthasagar (V), Hasanparthy (M) WERSINCAL - 506 371 (T.S.)

#### **ABSTRACT**

The switched-capacitor-based cascaded multilevel inverters (CMI) have been emerging due to their voltage boosting capability. Unfortunately, they suffer from impulse charging current and nonuniform operation. This article presents a topology termed as dual-T-type five-level CMI to resolve these problems without compromising the desirable voltage boosting characteristic. The main idea is to integrate a half bridge and an inductor to soft charge a capacitor that is connected in series with the dc source. The capacitor enables the voltage gain boosted to two, while the control of eight power switches that constitutes a dual-T structure enables five voltage levels generation. In addition, uniform operation is achieved for cascaded extensions. The operating principle of the proposed topology is analyzed and elaborated. For validation, simulation, and experimental results of a prototype are presented.



Principal Sumathi Reddy Institute of Technology for Women Ananthasagar (V), Hasanparthy (M) WARANGAL - 506 371 (TS)