

A
Project Report
On
AUTO BRAKING SYSTEM FOR VEHICLES USING ULTRASONIC SENSOR

Submitted to
Department of
ELECTRONICS & COMMUNICATION ENGINEERING

By

HUSNA HUMERA	216Y5A0410
VADNALA LAHARI	216Y5A0422
VURA AKHILA	206Y1A0461
P. GAYATHRI	206Y1A0447

Under the Esteemed Supervision of

Dr.K.Mahender
Associate Professor



DEPARTMENT OF ELECTRONICS & COMMUNICATION ENGINEERING
SUMATHI REDDY INSTITUTE OF TECHNOLOGY FOR WOMEN

(Approved by AICTE, New Delhi, Affiliated to JNTUH, Accredited by NBA)

Ananthasagar (Vill), Hasanparthy (M), Warangal.

2022-23



Rajam
PRINCIPAL

Sumathi Reddy Institute of Technology for Women
Ananthasagar (V), Hasanparthy (M)
WARANGAL - 506 371 (T.S.)



SUMATHI REDDY

INSTITUTE OF TECHNOLOGY FOR WOMEN

Learning at its best

Affiliated to JNTUH - Approved by AICTE - Accredited by NBA

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

CERTIFICATE

This is to certify that the project entitled "AUTO BRAKING SYSTEM FOR VEHICLES USING ULTRASONIC SENSOR" carried out by the following students of III Year B.Tech in Electronics and Communication Engineering during the academic year 2022-23.

HUSNA HUMERA 216Y5A0410

VADNALA LAHARI 216Y5A0422

VURA AKHILA 206Y1A0461

P. GAYATHRI **206Y1A0447**


Dr. K. Mahender
Supervisor


Dr. K. Mahender
Head of Department




PRINCIPAL
Sumathi Reddy Institute of Technology for Women
Ananthasagar (V), Hasanparthy (M)
WARANGAL - 506 371 (T.S.)

ABSTRACT

Drowsiness of the drivers is the main cause of accidents in the world. Due to lack of sleep and tiredness, drowsiness can occur while driving. This system alerts the user if he/she falls asleep at the wheel thereby, avoiding accidents and saving lives. This project involves measure and controls the eye blink using IR sensor. Here, we propose a method of detecting driver drowsiness using eye blink sensor. The primary purpose of the Drowsy Driver Detector is to develop a system that can reduce the number of accidents from sleep driving of vehicle. With our two monitoring steps, we can provide a more accurate detection. For the detecting stage, the eye blink sensor always monitors the eye blink moment. It continuously monitors eye blink. If the monitoring is over, the collected data will be transmitted to a microcontroller, and the microcontroller digitizes the analog data. If the warning feedback system is triggered, the microcontroller makes a decision which alert needs to be activated.



Rijan

Principal

Sumathi Reddy Institute of Technology for Women
Ananthasagar (V), Hasanparthy (M)
WARANGAL - 506 371 (TS)